Remolex Cables

CU REMOLEX 3X 10+4E

Contact
Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

Nexans Ref.: ENHP13AA003CXRJ
Country Ref.: 7025

Cu Conductors, PVC insulation, Laid up, Black PVC sheath, 450/750 V. Made to AS/NZS 5000.2. Circular multicore with integral earth.



DESCRIPTION

Application

- Industrial, commercial and domestic applications
- Small mains cables.

STANDARDS

National AS/NZS 5000.2

Conductor flexibility	Rated Voltage Uo/U (Um)	Cable flexibility	Max.conductor temp.in service	U.V resistance
Class 2	**450 / 750 V**	**Rigid**	**75 °C**	**Yes**

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Contact
Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

CHARACTERISTICS

Construction characteristics	
Conductor material	Copper
Type of conductor	Circular, stranded
Insulation	PVC
Outer sheath	PVC
Conductor flexibility	Class 2
Conductor shape	Circular
Core identification	Red, White, Blue, Green/Yellow
With Green/Yellow core	Yes
With smaller neutral conductor	No
Dimensional characteristics	
Number of cores	4
Conductor cross-section	10 mm²
Earth conductor cross section	4 mm²
Nominal overall diameter	16.6 mm
Gland Size (A2 or A2F)	25
Approximate weight	0.54 kg/m
Neutral conductor section (when smaller)	- mm²
Electrical characteristics	
Max. DC resistance of the conductor at 20°C (Ohm/km)	1.83
Rated Voltage Uo/U	450/750 V
Rated Voltage Uo/U (Um)	450 / 750 V
Mechanical characteristics	
Cable flexibility	Rigid
Usage characteristics	
Max. conductor temperature in service	75 °C
U.V resistance	Yes

CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - THREE & FOUR CORE REMOLEX PVC

Copper conductor Circular stranded Insulation PVC Max. Conductor Temperature 75C

Conductor cross-section						
[mm²]	Cu	Cu	Cu	Cu	Cu	Cu
10	62	58	50	61	61	29

Air Spaced from Surface, Unenclosed

Air touching, unenclosed

Air enclosed

Buried direct

Buried in single-way duct

Cable surrounded by thermal insulation, unenclosed

Note

© Copyright Standards New Zealand 2012.

Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Contact
Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz.

The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.