

LED VALUE STICK

We bring innovation to light!

Product licensee of trademark
OSRAM in general lighting



LED VALUE STICK



Item name	Product number (EAN)	W ¹		lm ¹	K	R _a		° ²		mm		d (mm)	t [h] ³
-----------	----------------------	----------------	--	-----------------	---	----------------	--	----------------	--	----	--	--------	--------------------

E27 Base

LED STICK	4058075020153	7	E27	700	2700	80	NO	200	115	41	10000
LED STICK	4058075020177	7	E27	750	4000	80	NO	200	115	41	10000
LED STICK	4058075020191	7	E27	750	6500	80	NO	200	115	41	10000
LED STICK	4058075020214	9	E27	900	2700	80	NO	200	115	41	10000
LED STICK	4058075020238	9	E27	950	4000	80	NO	200	115	41	10000
LED STICK	4058075020252	9	E27	950	6500	80	NO	200	115	41	10000
LED STICK	4058075020276	10	E27	1050	2700	80	NO	200	115	41	10000
LED STICK	4058075020290	10	E27	1100	4000	80	NO	200	115	41	10000
LED STICK	4058075020313	10	E27	1100	6500	80	NO	200	115	41	10000

B22 Base

LED STICK	4058075020337	7	B22	700	2700	80	NO	200	114	41	10000
LED STICK	4058075020351	7	B22	750	4000	80	NO	200	114	41	10000
LED STICK	4058075020375	7	B22	750	6500	80	NO	200	114	41	10000
LED STICK	4058075020399	9	B22	900	2700	80	NO	200	114	41	10000
LED STICK	4058075020412	9	B22	950	4000	80	NO	200	114	41	10000
LED STICK	4058075020436	9	B22	950	6500	80	NO	200	114	41	10000
LED STICK	4058075020450	10	B22	1050	2700	80	NO	200	114	41	10000
LED STICK	4058075020498	10	B22	1100	6500	80	NO	200	114	41	10000

Energy saving at a glance⁴

	≈		≈	
LED		incandescent		CFLI
7W		60W		12W
9W		70W		15W
10W		75W		20W

1.All technical parameters apply to the entire lamp. Because of the complex manufacturing process for light-emitting diodes (LEDs), the specified typical values for LED technical parameters represent only purely statistical variables. They do not necessarily correspond to the actual technical parameters for each individual product which can deviate from the typical value

2.LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

3.The average lifetime of LED lamps is defined as the number of hours when the light output of 50% of a large group of identical lamps goes below 70% of its initial luminous flux (L70B50, IEC62612).The lifetime is estimated at room temperature (25° C), free air burning, base up burning position and at rated voltage

LED VALUE STICK



Item name	Product number (EAN)	W ¹		lm ¹	K	R _a	 ²		 [mm]	 d [mm]	t [h] ³
-----------	----------------------	----------------	---	-----------------	---	----------------	---	---	---	---	--------------------

E26 Base

LED STICK	4058075022171	7	E26	700	2700	80	NO	200	112	41	10000
LED STICK	4058075022560	7	E26	750	4000	80	NO	200	112	41	10000
LED STICK	4058075022195	7	E26	750	6500	80	NO	200	112	41	10000
LED STICK	4058075022218	9	E26	900	2700	80	NO	200	112	41	10000
LED STICK	4058075022584	9	E26	950	4000	80	NO	200	112	41	10000
LED STICK	4058075022232	9	E26	950	6500	80	NO	200	112	41	10000
LED STICK	4058075022256	10	E26	1050	2700	80	NO	200	112	41	10000
LED STICK	4058075022607	10	E26	1100	4000	80	NO	200	112	41	10000
LED STICK	4058075022270	10	E26	1100	6500	80	NO	200	112	41	10000

Energy saving at a glance⁴

	≈		≈	
LED		incandescent		CFLi
7W		60W		12W
9W		70W		15W
10W		75W		20W

1.All technical parameters apply to the entire lamp. Because of the complex manufacturing process for light-emitting diodes (LEDs), the specified typical values for LED technical parameters represent only purely statistical variables. They do not necessarily correspond to the actual technical parameters for each individual product which can deviate from the typical value

2.LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

3.The average lifetime of LED lamps is defined as the number of hours when the light output of 50% of a large group of identical lamps goes below 70% of its initial luminous flux (L70B50, IEC62612).The lifetime is estimated at room temperature (25° C), free air burning, base up burning position and at rated voltage

SPEC are subject to change until final launch notification*

LED VALUE STICK



Benefits

- Saves 85% energy than incandescent and 40% energy than CFLi⁴
- Comfortable Light which bring instant nice ambiance
- Install and forget, super reliable quality created by over 100 years lighting brand.
- Slim cylindrical design fit elegantly in fixtures
- Modern Design, fit for different home styles

Key Features

- >100lm/W , super efficient
- Suitable for all kinds of E27, E26 and B22 fixtures.
- Instant brightness
- Super slim body
- UV and IR radiation free
- Mercury free

Application Note

- Suitable for indoor application.
- Switch off the light during installation
- For outdoor applications and operation in damp locations special approved fixture are required.
- Input voltage: 220-240V
- Storage temperature & humidity conditions (-20°C up to +80°C, at max. 95% relative humidity)
- Operating temperature & humidity conditions (-20°C up to +35°C, at max. 95% relative humidity)

1.All technical parameters apply to the entire lamp. Because of the complex manufacturing process for light-emitting diodes (LEDs), the specified typical values for LED technical parameters represent only purely statistical variables. They do not necessarily correspond to the actual technical parameters for each individual product which can deviate from the typical value

2 LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

3.The average lifetime of LED lamps is defined as the number of hours when the light output of 50% of a large group of identical lamps goes below 70% of its initial luminous flux (L70B50, IEC62612).The lifetime is estimated at room temperature (25° C), free air burning, base up burning position and at rated voltage.

4. Compare with standard Osram Incandescent lamp and CFLi lamp

LED VALUE STICK



Lamp conformity

- IEC 62560 Self-ballasted LED-lamps for general lighting services by voltage > 50 V – Safety specifications
- IEC 62471/ GB/T20145 Photo biological safety of lamps
- EN 55015 Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
- EN 61000-3-2 Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)
- EN 61000-3-3 Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection
- EN 61547 Equipment for general lighting purposes - EMC immunity requirements

Disposal information

- Lamps with WEEE sign can be returned at specific collection points.
- LED lamps have to be disposed as special waste.



SPEC are subject to change until final launch notification*



LEDVANCE GmbH
Parkring 33, 85748
Garching/Munich
Germany