PRODUCT DATASHEET
HALOPIN 40 W 240 V G9

HALOPIN Standard | Halogen lamps with G9 base



AREAS OF APPLICATION

- General illumination
- Workplace lighting
- Lighting for reading
- Dining table lighting
- Mirror lighting
- Accent lighting
- Mood lighting

PRODUCT BENEFITS

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Robust filament design thanks to innovative, unique bulb pinch technology
- Approved for use in open luminaires (to IEC 60598-1)
- Simple handling thanks to G9 plug-in base/holder system
- No transformer required
- UV filter
- Complies with IEC 60432-3 thanks to integrated fuse function
- The lamp shuts down reliably
- Contains no mercury

PRODUCT FEATURES

- Average life: 2,000 h
- Dimmable
- Color rendering index R_a: 100
- Design: two lengths 43 mm (short), 51 mm (long)
- Base: G9
- Color temperature: 2,700 K

© 2021, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	40.00 W
Nominal voltage	240 V
Rated wattage	40.00 W

Photometrical data

Nominal luminous flux	490 lm
Rated color temperature	2700 K
Light color (designation)	Warm White
Rated luminous flux	490 lm
Color rendering index Ra	100
Color temperature	2700 K
Luminous flux	490 lm
Color rendering index Ra	100

Light technical data

Starting time	0.0 s

Dimensions & weight



Diameter	14.0 mm
Length	42.5 mm
Light center length (LCL)	22.0 mm
Overall length	42.5 mm
Outer bulb	T13,3

Lifespan

Nominal lamp life time	2000 h
Rated lamp life time	2000 h

© 2021, LEDVANCE GmbH. All rights reserved.

Additional product data

Base (standard designation)	G9
Mercury-free	Yes
Product remark	Banned from 1.9.2011 as per EU phase-out plan

Capabilities

Burning position	Any
Dimmable	Yes

Country-specific categorizations

ILCOS	HSGST/C/UB-40-240-G9-22

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321826763	Folding carton box 1	25 mm x 23 mm x 70 mm	4.90 g	0.04 dm^3
4008321826770	Shipping carton box 20	144 mm x 55 mm x 118 mm	120.00 g	0.93 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2021, LEDVANCE GmbH. All rights reserved.