PRODUCT DATASHEET
DULUX D/E 18 W/3000K G24q-2

OSRAM DULUX D/E | CFLni, 2 tubes, with 4-pin base for ECG operation



AREAS OF APPLICATION

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

PRODUCT BENEFITS

- Extremly economical
- Good quality of light

PRODUCT FEATURES

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in G24q base

© 2021, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA


Electrical data

Rated wattage	18.00 W
Nominal wattage	18.00 W

Photometrical data

Light color (designation)	LUMILUX Cool White
Color temperature	3000 K

Dimensions & weight



Diameter	12.0 mm
Overall length	146.0 mm
Length	146.0 mm
Outer bulb	T11

Lifespan

Lifespan	10000 h [1)]

[1)] With preheat ECG

Additional product data

Base (standard designation)	G24q-2
Mercury content	2.5 mg

EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic control gear

© 2021, LEDVANCE GmbH. All rights reserved.

SAFETY ADVICE

In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830418	Folding carton box 1	36 mm x 36 mm x 160 mm	59.00 g	0.21 dm^3
4008321830425	Shipping carton box 10	187 mm x 81 mm x 175 mm	665.00 g	2.65 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2021, LEDVANCE GmbH. All rights reserved.