

PRODUCT DATASHEET

DULUX D 26 W/6500K G24d-3

OSRAM DULUX D | CFLni, 2 tubes, with 2-pin base for CCG operation



AREAS OF APPLICATION

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

PRODUCT BENEFITS

- Extremely economical
- Good quality of light
- Excellent luminous flux
- Long service life
- Improved maintenance

PRODUCT FEATURES

- Color rendering index $R_a : \geq 80$
- Short and compact pin-base lamp with double-turn tubes
- Single-ended two-pin plug-in G24d base



TECHNICAL DATA

Electrical data

Rated wattage	26.00 W
Nominal wattage	26.00 W

Photometrical data

Nominal luminous flux	1700 lm
Luminous flux at 25 °C	1710 lm
Rated luminous flux	1700 lm
Rated color temperature	6500 K
Color rendering index Ra	80...89
Rated LLMF at 2,000 h	0.77
Rated LLMF at 4,000 h	0.70
Rated LLMF at 6,000 h	0.69
Rated LLMF at 8,000 h	0.68
Color temperature	6500 K
Luminous flux	1700 lm
Color rendering index Ra	80...89

Dimensions & weight



Diameter	13.0 mm
Overall length	170.0 mm
Length	172.0 mm
Outer bulb	T4
Maximum diameter	11.0 mm

Lifespan

Nominal lamp life time	10000 h
Rated lamp life time	10000 h

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.81
Operation mode LLMF/LSF	50 Hz
Lifespan	10000 h ¹⁾

¹⁾ With CCG/LLCG

Additional product data

Base (standard designation)	G24d-3
Mercury content	1.3 mg

Capabilities

Suitable for indoor	Yes
---------------------	-----

Certificates & standards

Energy consumption	32 kWh/1000h
Energy efficiency class	B

EQUIPMENT / ACCESSORIES

- – Suitable for operation on conventional control gear

SAFETY ADVICE

In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830999	Folding carton box 1	36 mm x 36 mm x 179 mm	60.00 g	0.23 dm ³
4008321831002	Shipping carton box 10	187 mm x 81 mm x 196 mm	685.00 g	2.97 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.