Product data sheet
Characteristics

PDL306-WY
Iconic, cover frame with PIR Motion Sensor LED Light and Single GPO

Main

Range of product	Iconic
Range	PDL Iconic
Aesthetic name	Iconic
Product or component type	Cover frame
Colour tint	Warm grey (WY)
Type of packing	Polybag
Quantity per set	Set of 1

Complementary

Range compatibility	Switched socket
Product destination	Switched socket
Device mounting	Flush
Device composition	1 motion sensor 27 mA 1 LED light 8 mA 1 socket-outlet 10 A
Movement detection area	2 m
Presence detection area	1 m
Operating distance	2 m
Installation direction	Horizontal
Fixing mode	Plug-in
Surface finish	Matt
Height	78 mm
Width	120 mm
Depth	32 mm

Environment

Ambient air temperature for storage	-5…65 °C
Ambient air temperature for operation	0…45 °C
Relative humidity	10…85 %
Product certifications	RCM

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.064 kg
Package 1 Height	0.1 dm
Package 1 width	0.1 dm
Package 1 Length	0.1 dm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile