

Product data sheet

Specifications



Double USB socket, PDL Iconic, mechanism, 2.4A type A+C, 3A, 15W, vivid white

PDL342USB2AC-VW

Main

Range	PDL Iconic
Product or component type	USB charger
Colour tint	Vivid white
[Ue] rated operational voltage	220/240 V AC 50 Hz
Integrated connection type	1 USB type A 5 V DC, maximum load current: 2.4 A 1 USB type C, maximum load current: 3 A
maximum load current with 2 outputs used simultaneously	3.1 A

Complementary

Device mounting	Flush
Device presentation	Mechanism
Surface finish	Glossy
fixing mode	By clips
Type of packing	Box
Sale per indivisible quantity	1
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	5...90 %
Material	PC (polycarbonate)
Protection type	Short time short-circuit protection
Number of terminals	1 with cable end
Height	48 mm
Width	59 mm
Depth	59 mm
Embedding depth	55 mm
Type of USB power supply	USB type A + C
Connections - terminals	Screw terminals
Main colour tint	Vivid white
Fly-lead length	155 mm

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
Package 1 Height	3.9 cm
Package 1 Width	6.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	100 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	36 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	35 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	4
End of life manual availability	No need of specific recycling operations
Take-back	No