

Product data sheet

Specifications



Module Single USB Charger, Iconic, Type A, 1.5A, 300 Series

PDL342USB-VW

 To be discontinued on: 15 Aug 2026

 Discontinued

Main

Range	PDL Iconic
Product or component type	USB charger
Colour tint	Vivid white
[Ue] rated operational voltage	220/240 V AC 50 Hz
Integrated connection type	1 USB type A 5 V DC, maximum load current: 1.5 A
maximum load current with 2 outputs used simultaneously	1.5 A

Complementary

Device mounting	Flush
Device presentation	Mechanism
Surface finish	Glossy
fixing mode	By clips
Type of packing	Box
Sale per indivisible quantity	1
Ambient air temperature for operation	0...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	5...90 %
Material	PC (polycarbonate)
Number of terminals	3 screw terminal
Height	48 mm
Width	43 mm
Depth	43 mm
Embedding depth	38 mm
Type of USB power supply	USB type A
Connections - terminals	Screw terminals
Main colour tint	Vivid white

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	3.9 cm
Package 1 Width	6.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	90 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	36 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.9 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	35 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	4
End of life manual availability	No need of specific recycling operations
Take-back	No