Product data sheet
Characteristics

PDL342USB-VW
PDL Iconic, USB Charger



Main

Range	PDL Iconic
Product or component type	USB charger
Maximum load current with 2 outputs used simultaneously	1.5 A

Complementary

Device mounting	Flush
Device presentation	Mechanism
Surface finish	Glossy
Fixing mode	By clips
Type of packing	Box
Sale per indivisible quantity	1
Ambient air temperature for operation	0…45 °C
Ambient air temperature for storage	0…60 °C
Relative humidity	5…90 %
Height	48 mm
Width	27 mm
Depth	43 mm
Embedding depth	38 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	90 g
Package 1 Height	39 mm
Package 1 width	67 mm
Package 1 Length	87 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information