

Product data sheet

Specifications



Smart Remote 300 Series Module - ControlLink - 240 V - Vivid White

PDL356PBSS-VW

Main

Range	PDL Iconic
Product or component type	Timer
Device presentation	Mechanism
Colour tint	Vivid white

Complementary

Device mounting	Flush
Actuator	Push-button
fixing mode	Clip-in
Colour tint	Vivid white
Surface finish	Matt
Connections - terminals	screw terminals
Type of packing	Box
Sale per indivisible quantity	1
Remote control type	Push-button
[Ue] rated operational voltage	240 V AC 50 Hz
operating distance	30 m
Control signal type	ControlLink
Connections - terminals	Screw terminals
Number of terminals	2
Wiring configuration	2-wire
Screwdriver shape	Square drive no 1 (SQ1) Philips
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom
Height	22 mm
Width	22 mm
Depth	40 mm
Embedding depth	38 mm

Environment

Ambient air temperature for storage	0...60 °C
Ambient air temperature for operation	0...45 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative humidity	0...90 %
-------------------	----------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.9 cm
Package 1 Width	6.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	41 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	13 cm
Package 2 Width	9.6 cm
Package 2 Length	15.2 cm
Package 2 Weight	332 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0.5 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.1 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Halogen free product
PVC free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	24
End of life manual availability	No need of specific recycling operations
Take-back	No