Product data sheet
Characteristics

PDL395CSGZ
Connected Socket, Iconic, Zigbee default mode, Twin horizontal, 10 A, 240 V, Grid

Main

Range compatibility	Wiser hub PDL mounting bracket PDL wall box
Product brand	PDL
Range	Iconic
Product or component type	Socket-outlet

Complementary

Device presentation	Complete product
Socket-outlet type	Twin switched socket-outlet
[Ue] rated operational voltage	240 V AC 50 Hz
Colour tint	White
Surface finish	Matt
Local signalling	LED
Control type	Rocker on/off switching By mobile application
Software name	Wiser by SE App
Module configuration	Programmed with touch switch
Rated current	10 A
Technology type	Zigbee default Bluetooth low energy
Memory description	Backup memory - date and time for 6 h Backup memory - program for indefinite period
Material	Plastic
Type of installation	Indoor installation

Environment

IP degree of protection	IP20
Relative humidity	5…90 % non-condensing
Standards	AS/NZS 3112 safety AS/NZS 60669.2.1 safety AS/NZS 60669.2.1 EMC AS/NZS 4268 radio

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	202 g
Package 1 Height	5.4 cm
Package 1 width	9.5 cm
Package 1 Length	14.1 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information