

Product data sheet

Specifications



Twin socket with USB Type C, PDL
Iconic, Fast charger, 25W, 10A,
220-240V, AC, vivid white

PDL395USBC-VW

Main

Range	PDL Iconic
Product or component type	Switched socket with USB charger
Type of USB power supply	USB type C
Integrated connection type	2 socket-outlet 220/230/240 V AC 1 USB type C DC
Number of power socket outlets	2
Colour tint	Vivid white
Type of packing	Polybag
Quantity per set	1 set of 10
Switch function	With ON/OFF function

Complementary

Device presentation	Complete product
Number of rocker	2
Device mounting	Flush
Installation direction	Horizontal
Rated current	10 A
[Ue] rated operational voltage	220...240 V
Clamping connection capacity	1 x 2.5...4 x 2.5 mm ² for stranded cable(s)
fixing mode	By screws
Surface finish	Matt
Wire stripping length	16 mm
Height	120 mm
Width	78 mm
Depth	55 mm
Fly-lead length	155 mm

Environment

Ambient air temperature for storage	0...60 °C
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	2.7 cm
Package 1 Length	4.7 cm
Package 1 Weight	105.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	21.8 cm
Package 2 Width	10.2 cm
Package 2 Length	14.65 cm
Package 2 Weight	552 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	7 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.8 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	6 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	43
End of life manual availability	No need of specific recycling operations
Take-back	No

Image of product / Alternate images

Alternative







