

Product data sheet

Specifications



Ceiling Rose, PDL Lighting and Accessories, 5A 4-Terminals 250VAC

PDL44WH

Main

Range of product	PDL Lighting and Accessories
Product or component type	Lamp holder
Quantity per set	Set of 20
Type of packing	Carton

Complementary

Material	Polycarbonate
Surface finish	Glossy
[In] rated current	5 A
[Ue] rated operational voltage	250 V 50 Hz
Network number of phases	1 phase
fixing mode	By screws
Device mounting	Surface
Diameter	71 mm
Height	37.3 mm
fixing center	52.1 mm
Connections - terminals	3 x 1.5 mm ² screw terminal

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	6.7 cm
Package 1 Length	6.7 cm
Package 1 Weight	0.044 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0.7 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.3 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Halogen free product
PVC free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	29
End of life manual availability	No need of specific recycling operations
Take-back	No