

Product data sheet

Specifications



Surface socket, Standard Series, 3pin, 10A, 230/240VAC, white

PDL51SSE

Main

Range of product	Standard Series
Device application	Surface mounted installation of electric cable
Product or component type	Socket-outlet
Outlet poles configuration	3P
Colour tint	White

Complementary

Material	Plastic
Surface finish	Glossy
[In] rated current	10 A
[Ue] rated operational voltage	230/240 V AC 50 Hz
Network number of phases	1 phase
Device mounting	Surface
Height	55 mm
Width	88 mm
Diameter	68 mm
fixing center	52 mm
Outlet standard	Australian
Connections - terminals	4 x 4 screw terminals
Network frequency	50 Hz
fixing mode	By screws
Connections - terminals	Screw terminals
Number of terminals	4

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.8 cm
Package 1 Width	6.9 cm
Package 1 Length	5.6 cm
Package 1 Weight	93 g
Unit Type of Package 2	BB1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 2	10
Package 2 Height	8 cm
Package 2 Width	10.5 cm
Package 2 Length	29.5 cm
Package 2 Weight	882 g
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	42.8 cm
Package 3 Width	31.5 cm
Package 3 Length	32.5 cm
Package 3 Weight	9.3 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0.5 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
Halogen-free status	Halogen free product
PVC free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	27
End of life manual availability	No need of specific recycling operations
Take-back	No

Image of product / Alternate images

Alternative







