

Product data sheet

Characteristics

PDL568

2-Way Lockable ON/OFF Keylock Switch; 16A, 250V, White



Main

Range of product	500 Series
Product or component type	Switch
Quantity per set	Set of 5
Type of packing	Carton
Colour tint	White
Motor M-rating AS3133	M50

Complementary

Control type	Key switch
Material	PC (polycarbonate)
Installation direction	Vertical
Surface finish	Gloss
Width	74 mm
Height	118 mm
Rated current	16 A/16 AX
[Ue] rated operational voltage	250 V AC 50 Hz
Network number of phases	1 phase
Number of gangs	1 gang
Number of poles	1
Connections - terminals	Screw terminal
Clamping connection capacity	2 x 2.5 mm ²
Marking	ON-OFF
Device mounting	Surface
Fixing center	84 mm

Environment

Ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

Packing Units

Package 1 Weight	0.099 kg
Package 1 Height	65.000 mm
Package 1 width	75.000 mm
Package 1 Length	120.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile