

Product data sheet

Characteristics

PDL56C310RCD30LERW

RCD Protected Socket, 20A, 240V, 3-Flat Pin, 1-Gang, Resistant White



Main

Range of product	56 Series™
Product or component type	Residual current device switch
Control type	Push-button

Complementary

Material	PBT (polybutylene terephthalate)
Colour tint	White
Surface finish	Gloss
Installation direction	Vertical
Width	95 mm
Height	191 mm
Rated current	10 A
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Network number of phases	1 phase
Number of gangs	2 gangs
Pin number	3
Device composition	Flat pin
Mounting mode	Surface mounted
Fixing center	84 x 180 mm
IP degree of protection	IP66
Ambient air temperature for operation	-10...40 °C
Quantity per set	Set of 2
Type of packing	Carton

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.47 kg
Package 1 Height	75 mm
Package 1 width	100 mm
Package 1 Length	200 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile