Product data sheet
Characteristics

PDL56CSC310
Cord Extension Socket, 10A, 250V, 3-Flat Pin, Clear/Orange



Main

Range of product	56 Series™
Product or component type	Socket
Material	Plastic

Complementary

Colour tint	Orange
Surface finish	Gloss
Rated current	10 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Network number of phases	1 phase
Pin number	3
Device composition	Flat pin
IP degree of protection	IP66
Ambient air temperature for operation	-40…55 °C
Cable cross section	7…10.6 mm²
Quantity per set	Set of 4
Type of packing	Carton

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.12 kg
Package 1 Height	60 mm
Package 1 width	60 mm
Package 1 Length	110 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile