

Product data sheet

Characteristics

PDL56CV315LEGY

Switched Socket, 16A, 250V, 3-Flat Pin, 2-Gang, 2-Pole, Grey



Main

Range of product	56 Series
Product or component type	Switched socket
Control type	Rotary
Colour tint	Grey

Complementary

Material	Plastic
Surface finish	Gloss
Installation direction	Vertical
Dimension type	Cover only
Rated current	16 AX
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Motor M-rating AS3133	M120
Network number of phases	1 phase
Number of gangs	2 gangs
Pin number	3
Device composition	Flat pin
Number of poles	2
IP degree of protection	IP66
Fixing center	84 x 180 mm
Device mounting	Surface
Width	95 mm
Height	191 mm
Quantity per set	Set of 2
Type of packing	Carton

Packing Units

Package 1 Weight	0.414 kg
Package 1 Height	60.000 mm
Package 1 width	95.000 mm
Package 1 Length	190.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile