

# Product data sheet

## Characteristics

# PDL56CV315LERO

Switched Socket, 16A, 250V, 3-Flat Pin, 2-Gang, 2-Pole, Resis Orange



## Main

|                           |                 |
|---------------------------|-----------------|
| Range of product          | 56 Series       |
| Product or component type | Switched socket |
| Control type              | Rotary          |
| Colour tint               | Orange          |

## Complementary

|                                |                                  |
|--------------------------------|----------------------------------|
| Material                       | PBT (polybutylene terephthalate) |
| Surface finish                 | Gloss                            |
| Installation direction         | Vertical                         |
| Dimension type                 | Cover only                       |
| Rated current                  | 16 AX                            |
| [Ue] rated operational voltage | 250 V                            |
| Network frequency              | 50 Hz                            |
| Motor M-rating AS3133          | M120                             |
| Network number of phases       | 1 phase                          |
| Number of gangs                | 2 gangs                          |
| Pin number                     | 3                                |
| Device composition             | Flat pin                         |
| Number of poles                | 2                                |
| IP degree of protection        | IP66                             |
| Fixing center                  | 84 x 180 mm                      |
| Device mounting                | Surface                          |
| Width                          | 95 mm                            |
| Height                         | 191 mm                           |
| Quantity per set               | Set of 2                         |
| Type of packing                | Carton                           |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 0.416 kg |
| Package 1 Height             | 60 mm    |
| Package 1 width              | 95 mm    |
| Package 1 Length             | 190 mm   |

Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                           |
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                             |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |