

Product data sheet

Characteristics

PDL56CV320LERO

Switched Socket, 20A, 250V, 3-Round Pin, 2-Gang, 2-Pole, Resis Orange



Main

Range of product	56 Series
Product or component type	Switched socket
Control type	Rotary
Colour tint	Orange

Complementary

Material	PBT (polybutylene terephthalate)
Surface finish	Gloss
Installation direction	Vertical
Dimension type	Cover only
Rated current	20 AX
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Motor M-rating AS3133	M150
Network number of phases	1 phase
Number of gangs	2 gangs
Pin number	3
Device composition	Round pin
Number of poles	2
IP degree of protection	IP66
Fixing center	84 x 180 mm
Device mounting	Surface
Width	95 mm
Height	191 mm
Quantity per set	Set of 2
Type of packing	Carton

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.462 kg
Package 1 Height	55 mm
Package 1 width	95 mm
Package 1 Length	190 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile