Product data sheet
Characteristics

PDL56P416
Plug - Straight, 16A, 500V, 4-Round Pin, Clear/ Orange



Main

Range	56 Series
Product or component type	Plug

Complementary

Rated current	16 A
[Ue] rated operational voltage	500 V
Material	Plastic
Colour tint	Orange
Surface finish	Gloss
Network frequency	50 Hz
Network number of phases	3 phases
Pin number	4
Ambient air temperature for operation	-40…55 °C
Cable cross section	7…16 mm²
Quantity per set	Set of 4
Type of packing	Carton

Environment

IP degree of protection	IP66

Packing Units

Package 1 Weight	0.269 kg
Package 1 Height	75.000 mm
Package 1 width	75.000 mm
Package 1 Length	170.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile