Product data sheet
Characteristics

PDL56SO316/240LERW
Socket - Twin, 10A, 250V, 2-Gang, 3- Flat Pin, Resistant Orange

Main

Range of product	56 Series™
Product brand	PDL
Product or component type	Socket-outlet
Quantity per set	Set of 2
Type of packing	Carton

Complementary

Material	PC + PET
Colour tint	White
Surface finish	Gloss
Installation direction	Vertical
Width	95 mm
Height	191 mm
Depth	35 mm
Rated current	16 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Network number of phases	1 phase
Number of gangs	2 gangs
Pin number	3
Device composition	Round pin
Mounting mode	Surface mounted
Fixing center	84 x 84 mm
Cable cross section	0.75…10 mm²

Environment

IP degree of protection	IP66
Ambient air temperature for operation	-40…55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	230.484 g
Package 1 Height	35 mm
Package 1 width	95 mm
Package 1 Length	191 mm
Unit Type of Package 2	BB1
Number of Units in Package 2	4

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Weight	1.021 kg
Package 2 Height	8.3 cm
Package 2 width	19.2 cm
Package 2 Length	19.2 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	8
Package 3 Weight	2.2 kg
Package 3 Height	20 cm
Package 3 width	18 cm
Package 3 Length	22 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile