Product data sheet
Characteristics

PDL56SO410LECG
56 Series Socket - 4 Pin - 10A - 500V - Less Enclosure - Chemical Grey

Main

Product or component type	Socket-outlet
Device short name	PDL56SO410LECG
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard	Australian/New Zealand

Complementary

Mounting mode	Surface mounted
Plug, socket, control station shape	Straight
[In] rated current	10 A
Pin number	4 pins
Shape of pin	Tubular
[Ue] rated operational voltage	500 V
Network frequency	50 Hz
Material	Polycarbonate: cover
Contacts material	Pins: brass
Connections - terminals	Screw terminals 1.5…6 mm² rigid or stranded cable
Wire stripping length	16 mm
Net weight	0.257 kg
Height	95.0 mm
Width	95.0 mm
Depth	60.0 mm
Colour	Dark grey

Environment

Standards	AS/NZS 3123
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-25…75 °C
Ambient air temperature for storage	-25…75 °C

Packing Units

Package 1 Weight	0.258 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.