

Product data sheet

Specifications



Switched Pendant Socket, 56 Series, 250V 15A 3-Flat Pin IP66

PDL56SPO315RW

Main

Range of product	56 Series™
Product or component type	Socket-outlet
Material	PBT (polybutylene terephthalate)

Complementary

Colour tint	White
Surface finish	Gloss
Rated current	15 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Motor M-rating AS3133	M50
Network number of phases	1 phase
Pin number	3
Device composition	Flat pin
Mounting mode	Pendant
IP degree of protection	IP66
Ambient air temperature for operation	-40...55 °C
Cable cross section	0.75...2.5 mm²
Quantity per set	Set of 4
Type of packing	Carton

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.64 cm
Package 1 Width	8.3 cm
Package 1 Length	16.91 cm
Package 1 Weight	325 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Recycled metal content at CR level	0
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
China RoHS Regulation	China RoHS declaration

Use Again

 Repack and remanufacture	
Take-back	No