

Product data sheet

Characteristics

PDL56SW15

Auxiliary Switch Contact, 15A, 250V, 1-Pole



Main

Range of product	56 Series™
Product or component type	Auxiliary contact
Control type	Rotary

Complementary

Material	PC (polycarbonate)
Contacts material	Silver nickel
Colour tint	White
Surface finish	Gloss
Rated current	15 A
[Ue] rated operational voltage	240 V
Network frequency	50 Hz
Network number of phases	1 phase
Number of gangs	1 gang
Number of poles	1
Mounting mode	Surface mounted
Ambient air temperature for operation	-40...55 °C
Auxiliary contact composition	1 NO/NC
Quantity per set	Set of 5
Type of packing	Carton

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.014 kg
Package 1 Height	20 mm
Package 1 width	65 mm
Package 1 Length	80 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile