

Product data sheet

Characteristics

PDL56SW320LERO

Switch, 20A, 415V, 3-Pole, Resistant Orange



Main

Range of product	56 Series™
Range	56 Series
Product brand	Clipsal
Product or component type	Rotary switch
Device application	Control
Colour tint	Orange
Motor M-rating AS3133	M150
Quantity per set	Set of 4
Type of packing	Carton

Complementary

Number of poles	3
Control type	Rotary
Material	PBT (polybutylene terephthalate)
Surface finish	Gloss
Installation direction	Vertical
Width	95 mm
Height	95 mm
Depth	48 mm
Rated current	20 A
[Ue] rated operational voltage	415 V
[Ui] rated insulation voltage	660 V
Network frequency	50 Hz
Network number of phases	3 phases
Number of gangs	1 gang
Mounting mode	Surface mounted
Fixing center	84 x 84 mm
Cable cross section	1...16 mm²

Environment

IP degree of protection	IP66
Ambient air temperature for operation	-40...55 °C

Packing Units

Package 1 Weight	0.239 kg
Package 1 Height	60.000 mm
Package 1 width	95.000 mm
Package 1 Length	95.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile