

Product data sheet

Characteristics

PDL56SWB3322KGLERO

Switch - Base Mount, 32A, 415V, 3-Pole, 2-Gang, Resistant Orange



Main

Range of product	56 Series™
Product or component type	Rotary switch
Control type	Rotary

Complementary

Material	PBT (polybutylene terephthalate)
Colour tint	Orange
Surface finish	Gloss
Installation direction	Vertical
Width	95 mm
Height	190 mm
Depth	66 mm
Rated current	32 A
[Ue] rated operational voltage	240 V
Nominal power	7.5 KW 11 kW
Utilisation category	AC-23A AC-3
Network frequency	50 Hz
Motor M-rating AS3133	M180
Number of gangs	2 gangs
Number of poles	3
Mounting mode	Surface mounted
Fixing center	180 X 84 mm
IP degree of protection	IP66
Ambient air temperature for operation	-40...55 °C
Cable cross section	6 mm²
Quantity per set	Set of 1
Type of packing	Carton

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.462 kg
Package 1 Height	115 mm
Package 1 width	105 mm
Package 1 Length	213 mm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins