Product data sheet
Characteristics

PDL573R
1 Aperture Surface Switch Plate; White



Main

Range of product	500 Series
Product or component type	Switch
Quantity per set	Set of 20
Type of packing	Carton
Colour tint	White

Complementary

Material	PC (polycarbonate)
Installation direction	Vertical
Surface finish	Gloss
Diameter	66 mm
[Ue] rated operational voltage	250 V AC 50 Hz
[In] rated current	10 A
Network number of phases	1 phase
Number of gangs	1 gang
Pin number	3
Device mounting	Surface

Environment

Ambient air temperature for operation	-10…40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.027 kg
Package 1 Height	35 mm
Package 1 width	70 mm
Package 1 Length	70 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile