

# Product data sheet

## Characteristics

# PDL681M20LBK

## 681M20L BLACK MODULE LIGHT



### Main

|                           |            |
|---------------------------|------------|
| Range of product          | 600 Series |
| Product or component type | Switch     |
| Control type              | Rocker     |

### Complementary

|                                       |                                                    |
|---------------------------------------|----------------------------------------------------|
| Material                              | PC (polycarbonate)                                 |
| Colour tint                           | Black                                              |
| Surface finish                        | Gloss                                              |
| Installation direction                | Horizontal<br>Vertical                             |
| Length                                | 23 mm                                              |
| Width                                 | 23 mm                                              |
| Depth                                 | 26 mm                                              |
| Rated current                         | 16 AX<br>20 A                                      |
| [Ue] rated operational voltage        | 250 V                                              |
| Network type                          | AC                                                 |
| Motor M-rating AS3133                 | M60                                                |
| Network number of phases              | 1 phase                                            |
| Number of gangs                       | 1 gang                                             |
| Number of poles                       | 1                                                  |
| Mounting mode                         | Front                                              |
| Ambient air temperature for operation | -10...40 °C                                        |
| Cable cross section                   | 2 x 2.5 mm <sup>2</sup><br>4 x 1.5 mm <sup>2</sup> |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 0.014 kg |
| Package 1 Height             | 30 mm    |
| Package 1 width              | 23 mm    |
| Package 1 Length             | 23 mm    |

Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                           |
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                             |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |