Product data sheet

Specifications

Cover Plate Double Switched Socket, 600 Series, Vertical

PDL692MPB

To be discontinued on: 15 Aug 2026

Discontinued

Main

Range of product	600 Series
Product or component type	Cover plate
Colour tint	Polished brass
Quantity per set	Set of 10
Type of packing	Carton

Complementary

Product destination	2 gangs vertical switched socket
Material	Aluminium
surface treatment	Aluminium coated
Surface finish	Polished
Installation direction	Vertical
Width	74 mm
Height	118 mm
Mounting mode	Surface mounted

Environment

Ambient air temperature for operation	-10…40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.0 cm
Package 1 Width	7.5 cm
Package 1 Length	12.0 cm
Package 1 Weight	0.017 kg

Contractual warranty

Warranty (in months)	18

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Environmental footprint

Total lifecycle Carbon footprint	**5 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.1 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**5 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0 kg CO2 eq.**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
Halogen-free status	**Halogen free product**
PVC free	**No**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**15**
Take-back	**No**