

Product data sheet

Specifications



Socket Switch, Iconic Outdoor, Horizontal Twin 10A 250V

PDLO395-XW

Main

Range of product	Iconic
Range	Iconic
Product or component type	Switched socket
Device presentation	Complete product
Product brand	PDL
Outlet poles configuration	1P + E
Outlet standard	Australian
Main colour tint	Extra white
Switch application	On/off switching

Complementary

Socket-outlet type	Twin switched socket-outlet
Control type	Rocker
Device mounting	Wall mounted
Mounting position	Horizontal
Number of power socket outlets	2
Number of rocker	2
Range compatibility	Iconic
Outlet standard description	With earthing contact
Outlet standard deviation	Australian/New Zealand
Pin number	6
fixing mode	By screw
Installation direction	Horizontal
Surface finish	Matt
Type of packing	Box
Sale per indivisible quantity	1
Rated current	10 A at 230/240 V AC 50 Hz
Electrical durability	12000 cycles
Connections - terminals	3 screw terminals
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Clamping connection capacity	4 x 2.5 mm² 4 x 4 mm² 3 x 4 mm²
Wire stripping length	16 mm
Material	PC (polycarbonate) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene)
Type of installation	Outdoor
Height	85 mm
Width	115.5 mm
Depth	70 mm
Product weight	0.24 kg
[Ue] rated operational voltage	230/240 V

Environment

Ambient air temperature for storage	0...60 °C
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Standards	AS/NZS 3112
Product certifications	RCM
IP degree of protection	IP54

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.7 cm
Package 1 Width	11.9 cm
Package 1 Length	8.9 cm
Package 1 Weight	222.0 g
Unit Type of Package 2	BB2
Number of Units in Package 2	30
Package 2 Height	30.9 cm
Package 2 Width	41.3 cm
Package 2 Length	45.9 cm
Package 2 Weight	7.66 kg
Unit Type of Package 3	P06
Number of Units in Package 3	360
Package 3 Height	105.0 cm
Package 3 Width	60.0 cm
Package 3 Length	80.0 cm
Package 3 Weight	100.42 kg

Contractual warranty



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	23 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.6 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Halogen free product
PVC free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again





Repack and remanufacture

Recyclability potential, in %	12
End of life manual availability	End of Life Information
Take-back	No

Image of product / Alternate images

Alternative










Image of product in real life situation

