

Product data sheet

Specifications



Switch + PCU Unit, Pro Series, 20A 16AX 1/2-Way Vertical

PDLP351-XW

Main

Range	Pro Series
Product or component type	Switch
Device application	Switching loads
Number of rocker	1
Installation direction	Vertical
Colour tint	White
Quantity per set	Set of 10

Complementary

Device presentation	Complete product
Technology type	Electromechanical
Device mounting	Flush
[Ue] rated operational voltage	230/240 V
Network type	AC
Rated current	20 A/16 AX
surface treatment	Untreated
Surface finish	Glossy
Clamping connection capacity	1 x 1.5...4 x 1.5 mm² for rigid or stranded cable(s) 3 x 2.5 mm² for stranded cable(s) 1 x 4 mm² for stranded cable(s)
Fixing mode	By screws
Material	PC (polycarbonate)
Width	72 mm
Height	116 mm
Depth	21 mm
Net weight	74 g

Environment

Relative humidity	10...95 %
Ambient air temperature for operation	0...45 °C

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	7.8 cm
Package 1 Length	11.6 cm
Package 1 Weight	43.53 g

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	4
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No