Product data sheet
Characteristics

PDLP380M32O-XW
Pro Series, switch, 300M, marked OVEN, 32 A,White

Main

Range	Pro Series
Product or component type	Switch
Provided equipment	Rocker
Colour tint	White
Type of packing	Polybag
Quantity per set	Set of 10

Complementary

Device presentation	Mechanism with central plate
Control type	Rocker
Switch function	1-pole 1-way
Marking	Oven
Rated current	32 A
[Ue] rated operational voltage	250 V
Material	PC (polycarbonate) PA66 ABS (acrylonitrile butadiene-styrene)
Fixing mode	By clips
Surface finish	Glossy
Surface treatment	Untreated
Connections - terminals	Screw terminal
Clamping connection capacity	1 x 1.5...4 x 1.5 mm² for rigid or stranded cable(s) 3 x 2.5 mm² for stranded cable(s) 1 x 4 mm² for stranded cable(s)
Height	23 mm
Width	23 mm
Depth	32 mm
Net weight	0.01 kg

Environment

Ambient air temperature for operation	0…45 °C
Relative humidity	10…95 %
Product certifications	RCM

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	20.98 g
Package 1 Height	2.2 cm
Package 1 width	2.2 cm
Package 1 Length	2.4 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.