

Product data sheet

Specifications



Double switched socket, Pro Series, RCD, 30mA, 10A, horizontal, extra white

PDLP395RCD30V2-XW

Main

Range	Pro Series
Product or component type	RCD socket
Device presentation	Complete product
Product brand	PDL
Outlet poles configuration	2P + E with shutter
Outlet standard	Australian
Colour tint	Extra white
Main colour tint	Extra white

Complementary

Socket-outlet type	Double socket-outlet
Control type	Rocker
Device mounting	Wall mounted
Number of power socket outlets	2
Number of rocker	2
Range compatibility	Pro Series
Outlet standard description	With earthing contact
Outlet standard deviation	Australian/New Zealand
Ground lug position	Straight 180° position
Fixing mode	By screws
Installation direction	Horizontal
Local signalling	LED indicator
Surface finish	Glossy
surface treatment	Untreated
Sale per indivisible quantity	1
Connections - terminals	3 screw terminals
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Clamping connection capacity	1 x 2.5...4 x 2.5 mm² for rigid or stranded cable(s) 3 x 4 mm² for rigid or stranded cable(s)
Wire stripping length	16 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Material	PC (polycarbonate): fixing frame PP (polypropylene) POM (polyoxymethylene): shutter PC (polycarbonate): window ABS (acrylonitrile butadiene-styrene): infill piece ABS (acrylonitrile butadiene-styrene): skin
Type of installation	Indoor installation
Height	78.2 mm
Width	116 mm
Fixing center	84 mm
Depth	43.6 mm
Net weight	94 g
Earth-leakage protection class	Type II Type A
Trip unit rating	30 mA
Network frequency	50 Hz
[Ue] rated operational voltage	230...240 V
Local signalling	LEDs
Rated current	10 A
Network type	AC
Connections - terminals	3 pins
Number of terminals	3
Socket number	2

Environment

Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Standards	AS/NZS 3190 AS/NZS 3100 ISO 22196
Product certifications	RCM
IK degree of protection	IK08
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	8.1 cm
Package 1 Length	12.6 cm
Package 1 Weight	213 g
Unit Type of Package 2	CAR
Number of Units in Package 2	32
Package 2 Height	22.4 cm
Package 2 Width	26.1 cm

Package 2 Length	33.5 cm
Package 2 Weight	6.5 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	1536
Package 3 Height	95 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	334.8 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	182
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Recycled metal content at CR level	0
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration

Use Again

 Repack and remanufacture	
Circularity Profile	End of Life Information

Image of product / Alternate images

Alternative







