

Product data sheet

Specifications



Switch, Iconic, Assembled, vertical, 1_2way, 4 gangs, 20A, 230/240V, crowne

PDLS384-CE

Main

Range	Iconic
Product or component type	Switch
Device application	Switching loads
Number of rocker	4
Switch function	1/2-way
Colour tint	Crowne (CE)

Complementary

Device presentation	Complete product
Device mounting	Flush
Actuator	Rocker
Switch application	Switch
[Ue] rated operational voltage	230/240 V
Network type	AC
Network frequency	50 Hz
Rated current	20 A/16 AX
surface treatment	Anodised
Surface finish	Glossy
Connections - terminals	Screw terminals
fixing mode	By screws
Material	Metal
Width	126 mm
Height	82 mm
Depth	39.5 mm
Embedding depth	31 mm

Environment

Product certifications	RCM
Ambient air temperature for operation	0...45 °C

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
Package 1 Height	5.3 cm
Package 1 Width	15 cm
Package 1 Length	10.2 cm
Package 1 Weight	198 g
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	23 cm
Package 2 Width	26.7 cm
Package 2 Length	34.1 cm
Package 2 Weight	4.26 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	5 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Halogen free product
PVC free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	36
End of life manual availability	No need of specific recycling operations
Take-back	No

Image of product / Alternate images

Alternative







