

Product data sheet

Characteristics

PDLWSW201LEGY

Weather Protected Single Isolating Surface Switch; 20A, 1-Gang, Light Grey



Main

Range of product	WP Series
Product or component type	Switch
Switch function	1-pole 2-way
Control type	Rocker
Material	PC (polycarbonate)
Colour tint	Light grey

Complementary

Surface finish	Gloss
Installation direction	Horizontal
Width	84 mm
Height	84 mm
Depth	72 mm
Rated current	16 AX 20 A
Motor M-rating AS3133	M60
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Number of gangs	1 gang
Mounting mode	Surface mounted
IP degree of protection	IP56
Product specific application	Suits WE1 or WE1S enclosures
Clamping connection capacity	4 x 1.5 mm ² 2 x 2.5 mm ²
Type of packing	Carton

Packing Units

Package 1 Weight	0.072 kg
Package 1 Height	45.000 mm
Package 1 width	85.000 mm
Package 1 Length	85.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile