

LUMEN SELECT COLOUR SELECT




SLIMLINE OYSTER GEN3

PRODUCT DETAILS

- Lumen maintenance: L70 B50 60,000hrs
- LED: Colour Select 3000K/4000K/5700K, CRI80, 6SDCM
- Beam angle: Symmetrical, Back light halo feature
- Driver: Integral, Lumen Select (24W), Phase dimmable
- Rating: IP54, IK03, Class II
- Operating temperature: 0°C to +40°C
- Housing: Polycarbonate (PC), Low profile design
- Finishing: White
- Diffuser/Lens: Polycarbonate (PC), Opal
- Installation: Terminal block, large PA12 terminals and push-to-lock
- Warranty: 5 year

APPLICATIONS

Surface mounted, Internal
Residential, Ages Care, Hotel Accommodation, Apartments



CODE	DESCRIPTION	POWER	LUMENS	EFFICACY	WEIGHT
SL17W3/4/57KDG3	SLIMLINE 17W OYSTER 3/4/5700 CCT/LUMEN SELECT & PHASE DIMMING	17W	1800LM	106LM/W	0.8G
SL24W3/4/57KDG3	SLIMLINE 24W OYSTER 3/4/5700 CCT/LUMEN SELECT & PHASE DIMMING	24W	2500LM	106LM/W	1.3G
		17W	1800LM	104LM/W	

"POWER" is tested system powers from luminaire; "LUMENS" is delivered lumens from luminaire, including thermal, electrical and optic losses; ^Figures are interpolated / extrapolated from data at other versions.