

Weatherlux® LED

A versatile IP65 LED Picto Exit Luminaire, designed for 16M and 24M viewing distance in compliance with AS/NZ 2293.



Specifications

- Energy efficient lamp LED fluorescent
- Durable white polycarbonate body with quick connect removable gear tray
- Surface wall or ceiling mount with Pictogram 16m & 24m viewing distance complete polycarbonate diffuser available
- IP65 weatherproof construction
- Removable gear tray
- Tamper proof screws available as an option

Note: when ordering state diffuser option



Quick Spec

Pierlite Weatherlux LED Picto Exit, durable white polycarbonate body with quick connect removable gear tray, surface wall mount with Pictogram 16M / 24M viewing distance complete with polycarbonate diffuser.

Design Applications

Damp environments, warehouses, production facilities, car parks, schools and coastal areas.

Product Codes



Code	Version	Dim (mm)	Mass (kg)
WLLED	3W LED	365 x 150 x 60	2.5

Accessories

WL01P	16m Straight from here	365 x 150 x 55	0.3
WL02P	16m Left from here	365 x 150 x 55	0.3
WL03P	16m Right from here	365 x 150 x 55	0.3
WL04P	24m Straight from here	365 x 150 x 165	0.5
WL05PL	24m Single Sided Left	365 x 150 x 165	0.5
WL06PR	24m Single Sided Right	365 x 150 x 165	0.5
WL07DP	24m Double Sided	365 x 150 x 165	0.5
WL08DPR	24m Right from here	365 x 150 x 165	0.5
99026755	Bracket WLLED Wall Mount P/Coated		
99005988	Battery Pack NiCad AA size 1000MAH 4.8V		

Performance

Wall Mount



Ceiling Mount

