

CONSTRUCTION - XLPE CABLES 0.6/1 kV

4C+E XLPE CIRCULAR

X-90 XLPE INSULATED LAID UP AND PVC SHEATHED CABLE TO AS/NZS 5000.1.

For mains, submains and subcircuits unenclosed, in conduit, buried or in underground ducts for buildings and industrial plants where not subject to mechanical damage and where out of balance currents may require a neutral equal in size to the active. Suitable where space is at a premium and/or where conditions of overload may occur.




Cable Characteristics



Semi-rigid



OD≤25 4D
OD>25 6D



1



Water
Drops



Good



+90 °C
-15 °C



C3



Good

Cable Design

CONDUCTOR:

Plain annealed copper conductor to AS/NZS 1125
Maximum continuous operating temperature: 90 °C

INSULATION:

X-90 XLPE
Colours: Red, White, Blue, Black, Green


SHEATH:

5V-90 PVC
Colours: Orange


Installation Conditions




INDUSTRIAL
EQUIPMENT




OD≤25 6D
OD>25 9D




IN FREE AIR




IN
CONDUIT




MACHINES




0 °C



IN TRENCH



IN GROUND WITH
PROTECTION



IN DUCT



EXTERNAL
BUILDING

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.



CONSTRUCTION - XLPE CABLES 0.6/1 kV - 4C+E XLPE CIRCULAR**Physical & Electrical Characteristics**

Product code	Conductor			Cable				Min. installed bending radius mm
	Nominal C.S.A. mm ²	Number and diameter of wires No/mm	Nominal diameter mm	Nominal insulation thickness mm	Overall diameter mm		Approx. mass kg/100 m	
					Minimum	Maximum		
254CEXLP	25	19/1.35	6.8	0.9	24.0	25.1	132	150
354CEXLP	35	19/1.53	7.7	0.9	26.8	28.1	175	170
504CEXLP	50	19/1.78	8.9	1.0	30.8	32.2	237	190
704CEXLP	70	19/2.14	10.7	1.1	36.1	37.3	328	220
954CEXLP	95	19/2.45	12.5	1.1	40.6	42.1	439	250
1204CEXLP	120	37/2.03	14.2	1.2	45.3	46.7	550	280
1504CEXLP	150	37/2.25	15.8	1.4	50.7	52.3	684	310
1854CEXLP	185	37/2.52	17.6	1.6	57.0	58.6	862	350
2404CEXLP	240	61/2.25	20.3	1.7	64.4	66.2	1127	400
3004CEXLP	300	61/2.52	22.7	1.8	71.3	73.3	1407	440

Conductor nominal C.S.A. mm ²	Current rating (a)			Electrical characteristics	
	Unenclosed spaced A	Buried direct A	Underground in duct A	Maximum D.C. resistance at 20°C Ω/km	Reactance per core Ω/km
25	120	145	110	0.727	0.0808
35	145	170	135	0.524	0.0786
50	180	205	160	0.387	0.0751
70	230	250	200	0.268	0.0741
95	285	300	240	0.193	0.0725
120	330	345	275	0.153	0.0713
150	375	385	310	0.124	0.0718
185	435	435	355	0.0991	0.0720
240	520	500	420	0.0745	0.0709
300	590	570	475	0.0601	0.0704

(a) Based on 90 °C conductor temperature, 40 °C ambient air temperature and where applicable, burial depth of 0.5 m, soil temperature of 25 °C and soil thermal resistivity of 1.2 °C.m/W. Refer to AS/NZS 3008.1 for other installation conditions.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.



CABLE HANDLING

Cable Usage Characteristics

**AMBIENT TEMPERATURE**

Maximum operating temperature
Minimum operating temperature

**MECHANICAL IMPACT RESISTANCE**

1	Light Impact
2	Moderate Impact
3	Heavy Impact
4	Very Heavy Impact

**RESISTANCE TO SOLAR RADIATION AND WEATHER**

Excellent	Permanent
Very Good	Frequent
Good	Occasional
Acceptable	Accidental
Poor	None

**BEHAVIOUR IN FLAME AND FIRE**

Reaction To Fire	Resistant To Fire
C 1 Fire retardant	Level 1 Ultimate fire survival
C 2 Flame retardant	Level 2 Two hours fire survival
C 3 No fire performance	Level 3 Restrained spread & self extinguishing

**HALOGEN FREE**

AS/NZS 4507

**MINIMUM BENDING RADIUS**

Minimum bending radius of installed cables

**CHEMICAL RESISTANCE**

Excellent	Permanent
Very Good	Frequent
Good	Occasional
Acceptable	Accidental
Poor	None

**RESISTANCE TO WATER**

Negligible	No humidity
Water Drops	Occasional condensation
Spray	Water run off
Splashes	Exposed to water splashes
Heavy Sea	Exposed to waves
Immersion	Temporarily covered by water
Submersion	Permanently covered by water

**FLEXIBILITY**

Rigid	Flexible
Semi-rigid	Very flexible


**LOW SMOKE EMISSION**

AS/NZS 4507


Laying Conditions




MINIMUM BENDING RADIUS
DURING INSTALLATION



IN TRENCH




IN GROUND




IN DUCT




DOMESTIC
APPLIANCES




MACHINES




MOBILE
EQUIPMENT




SUBMERGED




OVERHEAD AERIAL




MIN. INSTALLATION
TEMPERATURE



IN FREE AIR



IN GROUND WITH
PROTECTION



IN CONDUIT



OUTDOOR
APPLIANCES



FESTOON



INTERNAL
WIRING



INDUSTRIAL
EQUIPMENT



EXTERNAL
BUILDING

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

