

DOWNLIGHTS



FEATURES & BENEFITS

These downlights are packed with everything you want, high lumen output, dimmable, quality assurance. With a replaceable trim. Designed for new homes and to replace incandescent and compact fluorescent down lights in existing homes. Sourced to the standards you demand in a residential downlight this range makes traditional light sources a thing of the past when building homes. IC-F Rated. Pre-selectable colour temperature - 3000k, 4000k & 5700k. Beam angles options available 90° and 100°

For technical details, see page 2


APPLICATIONS

Residential, Light Commercial

LIFETIME

L70 50,000hrs

Warranty 3 Years



DOWNLIGHTS

ORDER CODE	DESCRIPTION	CARTON QTY
REXDL8WCCT	Downlight LED 8W 3CCT 3/4/57k 90mm Cutout 720-830lm Flush Lens Terminal Block	24
REXDL8WCCTFL	Downlight LED 8W 3CCT 3/4/57k 90mm Cutout 720-830lm Flush Lens F&P	24
REXDL8WCCTFP	Downlight LED 8W 3CCT 3/4/57k 90mm Cutout 720-830lm Recessed Lens F&P	30

IDEAL CODE	REXDL8WCCT	REXDL8WCCTFL	REXDL8WCCTFP
WATTS	8W (Flush Lens)	8W (Recessed Lens, Flex & Plug)	8W (Flush Lens)
LUMEN OUTPUT	720-830lm	720-830lm	720-830lm
EFFICACY	90-103lm/w	90-103lm/w	90-103lm/w
COLOUR TEMPERATURE	3000K / 4000K / 5700K (Tri-colour)		
CRI	Ra >80		
BEAM ANGLE	90°	90°	100°
IP RATING	IP54		
IK RATING	IK06		
IES FILES AVAILABLE	Yes		
DIMMING / CONTROLS / DRIVERS	Triac Dimmable		
SDCM	<6		
LIFETIME	L70 50000Hrs		
WARRANTY	3 years		
CUT OUT SIZE	90-95mm		
DIMENSIONS	110×40mm	110×49.5mm	110×67.5mm
POWER FACTOR	≥0.9		
VOLTAGE & FREQUENCY	230V 50/60Hz		
WORKING TEMPERATURE	-20° -+ 45°C		
MATERIALS	Polycarbonate		
BODY COLOUR	White		
MOUNTING OPTIONS	Recessed		
APPLICABLE STANDARD/S	CE, RoHS, SAA		
CONNECTION E.G. FLEX & PLUG / TERMINAL	Terminal Block	1.5m flex and standard 3 pin plug	1.5m flex and standard 3 pin plug