



Features & Benefits

Backlit panel can be covered as it offers excellent thermal management with an IC-4 rating. The range includes a 4000K panel as well as a tri-colour option in all sizes. The panel also offers low glare UGR19.

Available in 600x600mm, 300x1200mm & 600x1200mm

Direct replacement for traditional 3x36W troffers.

Applications

Offices
Schools
Retail
Commercial

Lifetime

50,000 hours
5 year warranty




For technical details, see page 2

RX Backlit LED Panel V2

CODEW	REXBLP66V2	REXBLP123V2	REXBLP126V2
WATTS	36W	36W	60W
COLOUR TEMPERATURE	4000K		
LUMEN OUTPUT	2900lm	2900lm	4800lm
EFFICACY	80lm/W	80lm/W	80lm/W
CRI	CRI>90		
SDCM	<3		
BEAM ANGLE	90°		
IP RATING	IP44		
IK RATING	-		
IC RATING	IC-4		
IES FILES AVAILABLE?	Yes		
UGR	UGR19		
DIMMING	Non-dimmable		
LIFETIME	L80 50,000hrs B10		
WARRANTY	5 years		
DIMENSIONS	595x595x30mm	295x1195x30mm	595x1195x30mm
POWER FACTOR	0.9		
VOLTAGE & FREQUENCY	230V 50Hz		
WORKING TEMP	-20°C to +40°C		
WEIGHT	1.89kg	2.04kg	3.75kg
MATERIALS	Aluminum with PC diffuser		
FRAME COLOUR	White		
MOUNTING OPTIONS	Recessed		
STANDARDS & RATINGS	AS/NZS 60598 Part 2.2		
CONNECTION	Flex & Plug		

Photometric Diagrams



ORDER CODE	DESCRIPTION
REXBLP66V2	BACKLIT PANEL LED 600X600MM 36W 4K
REXBLP123V2	BACKLIT PANEL LED 1200X300MM 36W 4K
REXBLP126V2	BACKLIT PANEL LED 1200X600MM 60W 4K

ORDER CODE	DESCRIPTION	TO USE WITH MODEL
REXBLPDD36	BACKLIT PANEL DALI DRIVER 36W	REXBLP66V2, REXBLP66CCT, REXBLP123V2, REXBLP123CCT
REXBLPDD60	BACKLIT PANEL DALI DRIVER 60W	REXBLP126V2, REXBLP126CCT
REXBLPSMK66	BACKLIT PANEL SURFACE MOUNT KIT 600X600MM	REXBLP66V2, REXBLP66CCT
REXBLPSMK123	BACKLIT PANEL SURFACE MOUNT KIT 1200X300MM	REXBLP123V2, REXBLP123CCT
REXBLPSMK126	BACKLIT PANEL SURFACE MOUNT KIT 1200X600MM	REXBLP126V2, REXBLP126CCT

* Note: Dali Drivers to be ordered as an accessory to the standard Backlit Panel