



Features

This IP65 Polycarbonate LED weatherproof fitting, brings a new level of value. Featuring security clips that can be screwed closed, or stainless steel clips for longevity this product will meet your demands.

Perfect for loading docks, chillers or under eaves this product will give you significant energy and maintenance savings.

Operating Temperature -20 degrees to +30 degrees

Colour Temperature 4000K

Benefits:

- Clips to support the gear tray during installation
- Quick connect gear tray
- Anti vandal clips
- Low glare diffuser

Applications

Commercial

Lifetime

2 Year Guarantee

L70 30,000 Hours



For technical details, see page 2

RX NIX LED

ORDER CODE	REXNIX12LED	REXNIX14LED	REXNIX15LED	REXNIX22LED	REXNIX24LED	REXNIX25LED
LUMEN OUTPUT	987lm	2011lm	2635lm	2012lm	4186lm	5002lm
WATTS	11.8W	22.7W	30.9W	22.8W	46.3W	55.2W
CCT & RX	4000k					
CRI	80					
IP RATING	IP65					
IK RATING	IK08					
IES FILES	Yes					
LIFETIME	30,000hrs					
WARRANTY	2 years					
DIMENSIONS	665mm x 89mm x 92mm	1265mm x 89mm x 92mm	1565mm x 89mm x 92mm	665mm x 130mm x 92mm	1265mm x 130mm x 92mm	1565mm x 130mm x 92mm
VOLTAGE & FREQ	230V 50Hz					
WORKING TEMP	-20° to +30°C					
MATERIALS	Polycarbonate					
BODY COLOUR	Grey					
MOUNTING OPTIONS	Surface					
CONNECTION	Terminal					

ORDER CODE	DESCRIPTION	STOCKED
REXNIX12LED	RX NIX UNDERVERANDAH LED 12 IP65 11.8W	Stocked in NZ
REXNIX14LED	RX NIX UNDERVERANDAH LED 14 IP65 23W	Stocked in NZ
REXNIX15LED	RX NIX UNDERVERANDAH LED 15 IP65 30W	Stocked in NZ
REXNIX22LED	RX NIX UNDERVERANDAH LED 22 IP65 23W	Stocked in NZ
REXNIX24LED	RX NIX UNDERVERANDAH LED 24 IP65 48W	Stocked in NZ
REXNIX25LED	RX NIX UNDERVERANDAH LED 25 IP65 58W	Stocked in NZ

RX NIX LED Emergency Maintained 2 hour duration


ORDER CODE	REXNIX22LEDEM	REXNIX24LEDEM	REXNIX25LEDEM
LUMEN OUTPUT STD	2012lm	4186lm	5002lm
WATTS STD	22.8W	46.3W	55.2W
LUMEN OUTPUT EM	499lm	530lm	508lm
WATTS EM	4W	4W	4W
DIMENSIONS	665mm x 130mm x 92mm	1265mm x 130mm x 92mm	1565mm x 130mm x 92mm
WARRANTY	2 years, 1 year for batteries		
WORKING TEMP	+10° to +30°C		

ORDER CODE	DESCRIPTION	STOCKED
REXNIX22LEDEM	RX NIX UNDERVERANDAH LED 22 23W IP65 EM MAINT	NZ Manufactured on request
REXNIX24LEDEM	RX NIX UNDERVERANDAH LED 24 48W IP65 EM MAINT	NZ Manufactured on request
REXNIX25LEDEM	RX NIX UNDERVERANDAH LED 25 58W IP65 EM MAINT	NZ Manufactured on request


Accessories

ORDER CODE	DESCRIPTION	STOCKED
REXNIXLEDSSCLIP	RX NIX UNDERVERANDAH LED STAINLESS STEEL CLIPS PK	STOCKED IN NZ


Photometric Diagrams




Typical Polar distribution
Standard Fittings



Typical Polar distribution
2ft Emergency



Typical Polar distribution
4ft Emergency



Typical Polar distribution
5ft Emergency