



Features

- Slim Profile from only 40mm deep
- IP54 Suitable for use in Bathrooms
- For indoor use only
- Dimmable and available in three wattages 12W, 18W, and 30W
- Sensor versions available in 12W & 18W
- Colour correctable changeable (3000K, 4000K, 5700K) available in 18W & 30W
- Uniform light on the surface
- Up to 70% savings in energy compared to traditional lamps sources
- Easy Fix Bracket system allows for quick installation

Benefits:

- Clips to support the gear tray during installation
- Quick connect gear tray
- Anti vandal clips
- Low glare diffuser

Applications

Residential, Commercial

Lifetime

40000 Hours

3 Year Warranty



For technical details, see page 2

RX Selene Oyster

TYPE	Round	Square
WATTS	18w, 30w	12w, 18w, 30w
LUMEN OUTPUT	1,620lm - 2,900lm	1,400lm - 2,900lm
CCT & RX	3000K, 4000K, 5700K	3000K, 4000K, 5700K
CRI	80	80
BEAM ANGLE	N/A	N/A
IP RATING	IP54	IP54
IK RATING	IK08	IK08
IC RATING	N/A	N/A
IES FILES AVAILABLE?	Yes	Yes
UGR	N/A	N/A
DIMMING / CONTROLS / DRIVER	Triac dimmable	Triac dimmable
LIFETIME	40,000hrs L70 B10	40,000hrs L70 B10
WARRANTY	3 Years	3 Years
DIMENSIONS L,W,H	300mm x 40 mm 300 mm x 48 mm (CCT changeable version)	250mm x 250mm x 40 mm 300mm x 300mm x 40 mm 400mm x 400mm x 51 mm
MATERIALS	Polycarbonate	Polycarbonate
BODY COLOUR	White	White
MOUNTING OPTIONS	Surface	Surface
CONNECTION EG FLEX & PLUG / TERMINAL	Terminal	Terminal

ORDER CODE	DESCRIPTION
REXSEL12WCWSQ	RX SELENE OYSTER LED SQ DIM SEN 4000K
REXSEL12WWWSQ	RX SELENE OYSTER LED SQ DIM SEN 3000K
REXSEL18CCTSQ	SELENE OYSTER SQUARE 18W 3 COLOUR 300X300X40MM WHITE IP54
REXSEL30CCTSQ	SELENE OYSTER SQUARE 30W 3 COLOUR 400X400X51MM WHITE IP54
REXSEL18WCCTDIM	RX SELENE OYSTER LED 18W RND CCT DIM 300X48MM WHITE IP54
REXSEL30WCCTDIM	RX SELENE OYSTER LED 30W RND CCT DIM 300X48MM WHITE IP54