

RX SELENE ROUND



FEATURES & BENEFITS

Suitable for all residential situations including bathrooms.
Led Button Type Luminaire, 18W and 25W options.
Interchangeable Colour Temperature 3000K, 4000K, 5700K with slide switch.
High Lumen Efficacy.
Dimmable, using Triac leading or trailing edge type dimmer.
IP54 dust and water ingress rated
IK10 Impact Rating
Double insulated, does not require an earth connection.
Easy fix bracket system to allow for quick installation.

For technical details, see page 2

APPLICATIONS

Home / Residential including Bathrooms.

General Lighting for;
Schools, Commercial Offices,
Corridors, Supermarkets,
Hotels, Motels, Stairwells
and more.

WARRANTY

3 Year Warranty



RX SELENE ROUND

WATTS	18w	25W
LUMEN OUTPUT	1800-2100lm	2100-2750lm
EFFICACY	102-115lm/w	106-130lm/w
COLOUR TEMPERATURE	3CCT (3000K / 4000K / 5700K)	3CCT (3000K / 4000K / 5700K)
CRI	CRI>80	CRI>80
LIFETIME	40,000hrs L70 B10	40,000hrs L70 B10
IP RATING	IP54	IP54
IK RATING	IK10	IK10
IES FILES AVAILABLE	Yes	Yes
DIMMING / CONTROLS / DRIVERS	Triac dimmable	Triac dimmable
WARRANTY	3 yr	3 yr
DIMENSIONS	Ø300mm x 48mm	Ø300mm x 48mm
MATERIALS	Polycarbonate	Polycarbonate
BODY COLOUR	White	White
MOUNTING OPTIONS	Surface	Surface

ORDER CODE	DESCRIPTION	CARTON QTY
REXSEL18CCTRD	RX SELENE OYSTER LED 18W RND CCT DIM Ø300mm x 48mm WHITE IP54	1
REXSEL25CCTRD	RX SELENE OYSTER LED 25W RND CCT DIM Ø300mm x 48mm WHITE IP54	1