

SLIMPAK BATTEN NARROW LED



FEATURES & BENEFITS

- 4000K/6500K selectable
- IP40
- IK08
- Tool-free installation
- Conduit entried

For technical details, see page 2

APPLICATIONS

Residential
Commercial
Hospitality
Hotels
School

WARRANTY

5 Year Warranty

LED predicted lifetime is
50,000 hours, L80



SLIMPAK BATTEN NARROW LED

ORDER CODE	DESCRIPTION	CARTON QTY
REXSLMLED18W	SLIMPAK BATTEN NARROW LED 18W 600MM BI COL 4000K & 6500K	4
REXSLMLED38W	SLIMPAK BATTEN NARROW LED 38W 1200MM BI COL 4000K & 6500K	4
REXSLMLED50W	SLIMPAK BATTEN NARROW LED 50W 1500MM BI COL 4000K & 6500K	4

IDEAL CODE	REXSLMLED18W	REXSLMLED38W	REXSLMLED50W
WATTS	18W	38W	50W
LUMEN OUTPUT	2400	5000	6500
EFFICACY			
CCT & RX	4000K / 6500K		
CRI	CRI>80		
BEAM ANGLE	120°		
IP RATING	IP40		
IK RATING	IK08		
IES FILES AVAILABLE?	Yes		
DIMMING / CONTROLS / DRIVER	Non - Dimmable		
LED LIFETIME	50,000hrs L80		
WARRANTY	5 years		
LENGTH	600mm / 2ft	1200mm / 4ft	1500mm / 5ft
POWER FACTOR	≥0.9		
VOLTAGE & FREQUENCY	220-240V~50/60Hz		
OPERATING TEMP	-20°C ~+40°C		
WEIGHT			
MATERIALS	Polycarbonate		
BODY COLOUR	White		
MOUNTING OPTIONS	Ceiling/ Wall		