# Product data sheet
## Characteristics

# C40S4TM320D
## Circuit breaker, ComPacT NSX400S DC, 100kA/750VDC, 4 poles, TM-DC trip unit 320A

### Main

| | |
|---|---|
| Range | ComPacT new generation |
| Product name | ComPacT NSX DC new generation |
| Device short name | NSX400S DC |
| Product or component type | Circuit breaker |
| Device application | Distribution |
| Poles description | 4P |
| Protected poles description | 4D |
| Neutral position | Left |
| [In] rated current | 320 A at 40 °C |
| [Ue] rated operational voltage | 750 V DC |
| Network type | DC |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation category | Category A |
| [Icu] rated ultimate short-circuit breaking capacity | 100 KA Icu at 24...125 V DC 1 pole conforming to IEC 60947-2<br>100 KA Icu at 250 V DC 1 pole conforming to IEC 60947-2<br>100 KA Icu at 500 V DC 2 poles in series conforming to IEC 60947-2<br>100 kA Icu at 750 V DC 3 poles in series conforming to IEC 60947-2 |
| Performance level | S 100 kA 500 V DC |
| Trip unit name | TM-DC |
| Trip unit technology | Thermal-magnetic |
| Trip unit protection functions | LI |
| Control type | Toggle |
| Circuit breaker mounting mode | Fixed |

### Complementary

| | |
|---|---|
| [Ui] rated insulation voltage | 750 V DC conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 8 kV conforming to IEC 60947-2 |
| [Ics] rated service short-circuit breaking capacity | 100 KA at 24...125 V DC conforming to IEC 60947-2<br>100 KA at 250 V DC conforming to IEC 60947-2<br>100 KA at 500 V DC conforming to IEC 60947-2<br>100 kA at 750 V DC conforming to IEC 60947-2 |
| Mechanical durability | 5000 cycles |
| Electrical durability | 2000 Cycles at 750 V In/2<br>1000 cycles at 750 V In |
| Mounting support | Backplate |
| Mounting position | Horizontal and vertical<br>Flat on the back |
| Upside connection | Front |
| Downside connection | Front |
| Connection pitch | 45 mm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---|---|
| Protection type | L : for overload protection (thermal)<br>I : for short-circuit protection (magnetic) |
| Trip unit rating | 320 A at 40 °C |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable |
| [Ir] long-time protection pick-up adjustment range | 0.7...1 x In |
| Long-time protection delay adjustment type tr | Fixed |
| Instantaneous protection pick-up adjustment type Ii | Adjustable |
| [Ii] instantaneous protection pick-up adjustment range | 2.5...5 x In |
| Earth-leakage protection | Without |
| Number of slots for electrical auxiliaries | 6 slot(s) |
| Width (W) | 185 mm |
| Height (H) | 255 mm |
| Depth (D) | 110 mm |
| Net weight | 8.4 kg |

## Environment

| | |
|---|---|
| Standards | EN/IEC 60947 |
| Product certifications | CCC<br>EAC<br>Marine |
| Overvoltage category | Class II |
| Electrical shock protection class | Class II |
| Pollution degree | 3 conforming to IEC 60664-1 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -25…70 °C |
| Ambient air temperature for storage | -50…85 °C |
| Relative humidity | 0…95 % |
| Operating altitude | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 14.7 cm |
| Package 1 Width | 20.0 cm |
| Package 1 Length | 29.1 cm |
| Package 1 Weight | 6.6 kg |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Halogen content performance | Halogen free plastic parts product |