# Product data sheet
## Characteristics

# CD25124N9
## MSC Chassis, Acti9, 3*(1P+N), 250A, 9mm for iSPN iDPN RCBOs and iARC AFDDs, 12 Poles, dual feed

### Main

| | |
|---|---|
| Range | Acti9 |
| Device short name | MSC |
| Product or component type | Chassis |
| Device application | Distribution |

### Complementary

| | |
|---|---|
| Range compatibility | Acti9 distribution board |
| [In] rated current | 250 A |
| Rated voltage | 415 V AC 50 Hz |
| Short-circuit withstand | 25 kA 0.1 s |
| [Ui] rated insulation voltage | 500 V |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Outgoer Pole capacity | 12 |
| Busbar pitch | 9 mm |
| Location of Feed | Dual feed |
| Length | 245 mm |
| Width | 215 mm |

### Environment

| | |
|---|---|
| Standards | AS/NZS 61439 |

### Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 1.85 kg |
| Package 1 Height | 9.5 cm |
| Package 1 Width | 24.5 cm |
| Package 1 Length | 33.4 cm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

| | |
|---|---|
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |