

Product data sheet

Characteristics

CD25244N9

MSC Chassis, Acti9, 3*(1P+N), 250A, 9mm
for iSPN iDPN RCBOs and iARC AFDDs, 24
Poles, dual feed

Main

Range	Acti9
Device short name	MSC
Product or component type	Chassis
Device application	Distribution

Complementary

Range compatibility	Acti9 distribution board
[In] rated current	250 A
Rated voltage	415 V AC 50 Hz
Short-circuit withstand	25 kA 0.1 s
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Outgoer Pole capacity	24
Busbar pitch	9 mm
Location of Feed	Dual feed
Length	245 mm
Width	215 mm

Environment

Standards	AS/NZS 61439
-----------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.0 kg
Package 1 Height	9.5 cm
Package 1 Width	24.5 cm
Package 1 Length	31.6 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration