Product data sheet
Characteristics

CD25724N9
MSC Chassis, Acti9, 3*(1P+N), 250A, 9mm for iSPN iDPN RCBOs and iARC AFDDs, 72 Poles, dual feed

Main

Range	Acti9
Device short name	MSC
Product or component type	Chassis
Device application	Distribution

Complementary

Range compatibility	Acti9 distribution board
[In] rated current	250 A
Rated voltage	415 V AC 50 Hz
Short-circuit withstand	25 kA 0.1 s
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Outgoer Pole capacity	72
Busbar pitch	9 mm
Location of Feed	Dual feed
Length	245 mm
Width	215 mm

Environment

Standards	AS/NZS 61439

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4.1 kg
Package 1 Height	9.5 cm
Package 1 Width	24.5 cm
Package 1 Length	60.4 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration