

Product data sheet

Characteristics

EVP1CNS32122

Charging cable, EVlink, 5m, 32A, 1-Phase, T2 connector at each end of cable



Main

Range	EVlink
Product or component type	Charging cable
Accessory / separate part category	Cabling accessory
Network number of phases	Single phase
Poles description	1P + N
[In] rated current	32 A
[Us] rated supply voltage	220...240 V AC 50/60 Hz
Socket number	2

Complementary

Plug type	T2 / silver plated contacts charging station end
Connector type	T2 vehicle end silver plated contacts T2 charging station end silver plated contacts
Range compatibility	EVlink parking EVF1 charging station EVlink parking EVW1 charging station EVlink parking EVF2 charging station EVlink parking EVW2 charging station EVlink Smart Wallbox EVB1 charging station EVlink Wallbox EVH2 charging station EVlink Pro AC EVB3 charging station EVlink Pro AC Metal EVB3 charging station
Standards	IEC 62196-2 IEC 62196-1
Product certifications	CE
Length	5 m
Net weight	2.5 kg
Colour	Grey

Environment

IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-30...50 °C
Ambient air temperature for storage	-40...80 °C
Relative humidity	5...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.313 kg
Package 1 Height	11 cm
Package 1 width	25 cm
Package 1 Length	33 cm
Unit Type of Package 2	S03
Number of Units in Package 2	3

Package 2 Weight	8.531 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	24
Package 3 Weight	76.748 kg
Package 3 Height	77 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration